

Dysze olejowe

Dysze olejowe HR i SR (wzorec rozpylania: H i S)

Minimalne zbiorcze opakowanie zawiera 10 szt.

Nr katalogowy	Typ	Opis
patrz tabela	HR/SR	USgal/h 0.30-0.35
patrz tabela	HR/SR	USgal/h 0.40-0.45
patrz tabela	HR/SR	USgal/h 0.50-1.75

	kg/h	45°	60°	80°	USgal/h
	1.15		030F7902	030F9902	0.30
	1.35		030F7903	030F9903	0.35
	1.46	030F5904	030F7904	030F9904	0.40
	1.66	030F5906	030F7906	030F9906	0.45
	1.87	030F5908	030F7908	030F9908	0.50
	2.11	030F5910	030F7910	030F9910	0.55
	2.37	030F5912	030F7912	030F9912	0.60
	2.67	030F5914	030F7914	030F9914	0.65
	2.94	030F5916	030F7916	030F9916	0.75
	3.31	030F5918	030F7918	030F9918	0.85
	3.72	030F5920	030F7920	030F9920	1.00
	4.24	030F5922	030F7922	030F9922	1.10
	4.45	030F5923	030F7923	030F9923	1.20
	4.71	030F5924	030F7924	030F9924	1.25
	5.17	030F5926	030F7926	030F9926	1.35
	5.84	030F5928	030F7928	030F9928	1.50
	6.08	030F5929	030F7929	030F9929	1.65
	6.55	030F5930	030F7930	030F9930	1.75
			030F7932		2.00
			030F7934		2.25
			030F7936		2.50
	kg/h	45°	60°	80°	USgal/h
	1.15		030H7902	030H9902	0.30
	1.35		030H7903	030H9903	0.35
	1.46		030H7904	030H9904	0.40
	1.66	030H5906	030H7906	030H9906	0.45
	1.87	030H5908	030H7908	030H9908	0.50
	2.11	030H5910	030H7910	030H9910	0.55
	2.37	030H5912	030H7912	030H9912	0.60
	2.67	030H5914	030H7914	030H9914	0.65
	2.94	030H5916	030H7916	030H9916	0.75
	3.31	030H5918	030H7918	030H9918	0.85
	3.72	030H5920	030H7920	030H9920	1.00
	4.24	030H5922	030H7922	030H9922	1.10
	4.45	030H5923	030H7923	030H9923	1.20
	4.71	030H5924	030H7924	030H9924	1.25
	5.17	030H5926	030H7926	030H9926	1.35
	5.84	030H5928	030H7928	030H9928	1.50
	6.08	030H5929	030H7929	030H9929	1.65
	6.55	030H5930	030H7930	030H9930	1.75